

FREE STANDING ENCLOSURES

Double Door (IP41/IP55) | IK10

PAINT : RAL7035W Electrostatic Powder Coating (Salt spray test up to 600 hours)
C5M paint optional

GASKET : Poliuretanan Liquid Gasket

PROTECTION : IP41/IP55 (Double Door) - IK10

AVAILABLE DIMENSIONS :

Width : 1000-1200mm / Height : 1600-2200 mm / Depth : 400-800 mm
Height dimensions includes 100 mm floorbase (plinth)

DOOR : Rod Latch Lock Systems and Concealed Hinge
Front door can be open up to 105° - 3 point locking system.

MATERIAL:

Cargass : 1,5 mm galvanized steel.
Door : 2 mm painted steel
Rear, roof and side panels : 1,2 mm painted steel
Mounting Plate : 2mm galvanized steel
Internal Parts: 1,5 mm galvanized steel
Bottom Plates : 1,2 mm galvanized steel
Base Corner: 2,0 mm Painted steel

SIDE PANELS:

Supplied as an accessory

ROOF PANEL : Removable

LOCK : Espagnolette 3-points locking system.

BOTTOM PLATES : Consists of three pieces.

MOUNTING PLATE : Supplied as an accessory with multiple size options

EARTHING : All panels are earthed through their fittings and are equipped with a separate earthing stud.

CERTIFICATES : CE, IEC,TSE,ISO,GOST,SEISMIC

DELIVERY : Frame with fitted door, rear panel, roof panel, bottom plates.Delivery also includes earthing bolts.
Package includes two CMB profiles mounted in depth. . All packing material is recyclable.Delivery will be in cartoon boxes combined in pallets.