

FREE STANDING ENCLOSURES

Welded Type (IP65) | IK10

PAINT : RAL7035W Electrostatic Powder Coating (Salt spray test up to 600 hours)
C5M paint optional

GASKET : Poliuretana Liquid Gasket

PROTECTION : IP65 (Outdoor Type) - IK10

AVAILABLE DIMENSIONS :

Width : 400-800mm / Height : 1600-2200 mm / Depth : 300-400 mm
Height dimensions includes 100 mm floorbase (plinth)

DOOR : Rod Latch Lock Systems and Concealed Hinge
Front door can be open up to 105° - 3 point locking system.

MATERIAL :

Cargass : 1,5 mm galvanized steel.
Door : 2 mm painted steel
Rear : 1,2 mm painted steel
Mounting Plate : 2mm galvanized steel
Internal Parts: 1,5 mm galvanized steel
Bottom Plates : 1,2 mm galvanized steel
Base Corner: 2,0 mm Painted steel

SIDE PANELS :

Supplied as an accessory

LOCK : Espagnolette 3-points locking system.

BOTTOM PLATES : Consists of single part with gasket.

MOUNTING PLATE : Supplied as an accessory with multiple size options

EARTHING : All panels are earthed through their fittings and are equipped with a separate earthing stud.

CERTIFICATES : CE, IEC, TSE, ISO, GOST, SEISMIC

DELIVERY : Enclosures ship on the pallet and accessories will be install inside the panels if requested.